



Roca

Weston



CERAMIC

Weston

A Mesmerizing Hybrid of Marble's Elegance and Stone's Strength. Experience a unique textural journey, elevating spaces with timeless sophistication.

Ceramic Floor

◇ 12"x24" - 17"x17" - 13"x13"

Weston

Ceramic Floor



12"x24"
30x60 cm

17"x17"
44x44 cm


13"x13"
33x33 cm



White



17"x17"
UWESTON13CV



12"x24"
UWESTON16BV



13"x13"
UWESTON13CV



12"x12" Mosaic
UWESTO1212V




3"x24" Bullnose
UWESTON312V



Beige



17"x17"
UWESTON14HE



12"x24"
UWESTON16BE



13"x13"
UWESTON13CE




12"x12" Mosaic
UWESTO1212E



3"x24" Bullnose
UWESTON312E



Brown



17"x17"
UWESTON14HG



12"x24"
UWESTON16BG



13"x13"
UWESTON13CG



12"x12" Mosaic
UWESTO1212G



3"x24" Bullnose
UWESTON312G



Grey



17"x17"
UWESTON14HI



12"x24"
UWESTON16BI



13"x13"
UWESTON13CI



12"x12" Mosaic
UWESTO1212I



3"x24" Bullnose
UWESTON312I

Weston

Ceramic Floor

Technical Specifications

CHARACTERISTICS	STANDARD	DECLARED ASTM
Water Absorption	C373	3%<wa<7%
Break Strength	C648	Min. 250
Scratch Hardness	MOH's Scale	-
Chemical Resistance	C650	Unaffected
Frost Resistance	C1026	Not Resistant
Group	See FAQ's	2
Deep Abrasion - Unglazed Tiles	C1043	N/A
PEI- Glazed Tiles***	C1027	3
Minimum Bond Strength (PSI)	C482	165
Dynamic Coefficient of Friction (DCOF)	A137.1	>=0.42
Shade and Texture Rating	CTDA "V"	V2
Facial Dimensions	C499	Pass
Range of Thickness	C499	Pass
Warpage	C485	Pass
Wedging	C502	Pass

Packaging Information

Size	SF per carton	PC per carton	BX per pallet
13"x13"	16.47	14	72
12"x24"	19.38	10	32
17"x17"	16.58	8	48