



Roca

Terre



Terre Beige



Terre Beige



Terre Gráfico

Terre

Glazed Porcelain



24"x48" 60x120 cm
24"x24" 60x60 cm
12"x24" 30x60 cm



Blanco



24"x48" R
FDDR054011



24"x24" R
FDDR060011



12"x24" R
FDDR057011



Gris



24"x48" R
FDDR054021



24"x24" R
FDDR060021



12"x24" R
FDDR057021



Beige



24"x48" R
FDDR054041



24"x24" R
FDDR054041



12"x24" R
FDDR057041



Grafito



24"x48" R
FDDR054101



24"x24" R
FDDR054101



12"x24" R
FDDR057101

Terre

Glazed Porcelain


8.7-10
mm



12"x36" R
30x90 cm



Suite Bianco



12"x36" R
FDDR1AW011




Suite Beige



12"x36" R
FDDR1AW041



Suite Gris



12"x36" R
FDDR1AW021



Suite Grafito



12"x36" R
FDDR1AW101



Deko Beige



12"x36" R
FDDR2AW041



Deko Gris



12"x36" R
FDDR2AW041

Terre

Glazed Porcelain

Technical Specifications

CHARACTERISTICS	STANDARD	DECLARED ASTM
Water Absorption	ISO-10545/3	>10%
Break Strength	ISO-10545/4	Meets or Exceeds
Scratch Hardness	EN-101	N/A
Chemical Resistance	ISO-10545/13	Unaffected
Shade and Texture Rating	CTDA	V3
Warping	ISO-10545/2	Pass
Wedging	ISO-10545/2	Pass

Technical Specifications (Floor)

CHARACTERISTICS	STANDARD	DECLARED ASTM
Water Absorption	ISO-10545/3	<=0.5%
Break Strength	ISO-10545/4	290
Scratch Hardness	EN-101	7
Chemical Resistance	ISO-10545/13	Unaffected
Frost Resistance	ISO-10545/12	Resistant
Group	ISO-10545/7	4
PEI	C1027	5
Minimum Bond Strength (PSI)	C482	165
Dynamic Coefficient of Friction (DCOF)	A137.1	<=0.42
Shade and Texture Rating	CTDA	V3
Facial Dimensions	ISO-10545/2	Pass
Range of Thickness	ISO-10545/2	Pass
Warping	ISO-10545/2	Pass
Wedging	ISO-10545/2	Pass

Packaging Info

Size	SF per carton	PC per carton
12"x36" R	14.53	5

Packaging Info

Size	SF per carton	PC per carton
12"x24" R	13.56	7
24"x24" R	10.65	5
24"x48" R	14.53	5