

# AURA

## TECHNICAL DATA



11190 NW 25th Street, Suite 100  
MIAMI, FL 33172  
www.rocatileusa.com

|                  |                      |                   |                   |
|------------------|----------------------|-------------------|-------------------|
| Format:          | 4"X12"               | Type:             | Ceramic Wall Tile |
| Colors:          | All Colors Available | Thickness:        | 8.0 mm            |
| Number of faces: | 18                   | Recycled Content: | 25% *Pre-Consumer |

|                          | ASTM Test   | ISO Test     | Value Required ANSI | Declared ASTM  |
|--------------------------|-------------|--------------|---------------------|----------------|
| WATER ABSORPTION         | C373        | ISO.10545/3  | <7.0% < wa ≤20%     | ≤20%           |
| BREAKING STRENGTH        | C648        | ISO.10545/4  | ≥ 125               | Not Applicable |
| SCRATCH HARDNESS         | MOH's Scale | EN-101       | -                   | Not Applicable |
| CHEMICAL RESISTANCE      | C650        | ISO-10545/13 | Unaffected          | Unaffected     |
| SHADE AND TEXTURE RATING | CTDA "V"    | -            | -                   | V2             |
| WARPAGE                  | C485        | ISO-10545/2  | 0.75%               | Pass           |
| WEDGING                  | C502        | ISO-10545/2  | 1.0% Max            | Pass           |

\*Contains a percentage of pre-consumer recycled content superior to 25% which has been certified by Bureau Veritas.

Signature:  
Marketing and Product Department

  
MARKETING & PRODUCT DEPT  
11190 NW 25th Street, Suite 100  
MIAMI, FL 33172  
www.rocatileusa.com

Release  
12 / 29 / 2023