



11190 NW 25th Street, Suite 100
MIAMI, FL 33172
www.rocatileusa.com

LASSA WALL

TECHNICAL DATA

Format:	All formats available	Type:	Ceramic wall tile
Colors:	White	Thickness:	7.3 mm (3x12) 8.0 mm (6x18)
Number of faces:	37 (3X12) 18 (6X18)	Recycled Content:	25% *Pre -Consumer

	ASTM Test	ISO Test	Value Required ANSI	Declared ASTM
WATER ABSORPTION	C373	ISO.10545/3	<7.0% < wa ≤20%	≤20%
BREAKING STRENGTH	C648	ISO.10545/4	≥ 125	Not Applicable
SCRATCH HARDNESS	MOH's Scale	EN-101	-	Not Applicable
CHEMICAL RESISTANCE	C650	ISO-10545/13	Unaffected	Unaffected
SHADE AND TEXTURE RATING	CTDA "V"	-	-	VI
WARPAGE	C485	ISO-10545/2	0.75%	Pass
WEDGING	C502	ISO-10545/2	1.0% Max	Pass

*Contains a percentage of pre-consumer recycled content superior to 25% which has been certified by Bureau Veritas.

Signature:
Marketing and Product Department



Release Date
12 / 29 / 2023