



**Roca**

**Weston**



# Weston


A Mesmerizing Hybrid of Marble's Elegance and Stone's Strength. Experience a unique textural journey, elevating spaces with timeless sophistication.

Ceramic Floor

◇ 12"x24" - 17"x17" - 13"x13"

# Weston

Ceramic Floor




**12"x24"**  
30x60 cm

**17"x17"**  
44x44 cm

**13"x13"**  
33x33 cm



## White



**17"x17"**  
UWESTON13CV



**12"x24"**  
UWESTON16BV




**13"x13"**  
UWESTON13CV



**12"x12" Mosaic**  
UWESTO1212V



## Brown



**17"x17"**  
UWESTON14HG



**12"x24"**  
UWESTON16BG



**13"x13"**  
UWESTON13CG




**12"x12" Mosaic**  
UWESTO1212G



## Beige



**17"x17"**  
UWESTON14HE



**12"x24"**  
UWESTON16BE



**13"x13"**  
UWESTON13CE



**12"x12" Mosaic**  
UWESTO1212E



## Grey



**17"x17"**  
UWESTON14HI



**12"x24"**  
UWESTON16BI



**13"x13"**  
UWESTON13CI



**12"x12" Mosaic**  
UWESTO1212I

# Weston

## Ceramic Floor

---

### Technical Specifications

<b>CHARACTERISTICS</b>	<b>STANDARD</b>	<b>DECLARED ASTM</b>
Water Absorption	C373	3%<wa<7%
Break Strength	C648	Min. 250
Scratch Hardness	MOH's Scale	-
Chemical Resistance	C650	Unaffected
Frost Resistance	C1026	Not Resistant
Group	See FAQ's	2
Deep Abrasion - Unglazed Tiles	C1043	N/A
PEI- Glazed Tiles***	C1027	3
Minimum Bond Strength (PSI)	C482	165
Dynamic Coefficient of Friction (DCOF)	A137.1	>=0.42
Shade and Texture Rating	CTDA "V"	V2
Facial Dimensions	C499	Pass
Range of Thickness	C499	Pass
Warpage	C485	Pass
Wedging	C502	Pass

### Packaging Information

<b>Size</b>	<b>SF per carton</b>	<b>PC per carton</b>	<b>BX per pallet</b>
13"x13"	16.47	14	72
12"x24"	19.38	10	32
17"x17"	16.58	8	48