



Roca

Alaska

Alaska

The Alaska White boasts graceful gray veining which give rise to interesting contrasts between its delicate veins and its homogeneous white base, making it a perfect ally for interior design.



Alaska White PO 24"x48" R

Polished Porcelain

◇ 24"x48" R

Alaska

Polished Porcelain



24"x48" R
60x120 cm



White



24"x48" R PO
GFALAWH-2448PO

Technical Specifications

| CHARACTERISTICS | STANDARD | DECLARED ASTM |
|--|-------------|---------------|
| Water Absorption | C373 | <=0.5% |
| Break Strength | C648 | Min. 290 |
| Scratch Hardness | MOH's Scale | 3 |
| Chemical Resistance | C650 | Unaffected |
| Frost Resistance | C1026 | Resistant |
| Group | See FAQ's | 3 |
| Deep Abrasion - Unglazed Tiles | C1243 | Pass |
| PEI - Glazed Tiles | C1027 | 3 |
| Minimum Bond Strength (PSI) | C482 | 165 |
| Dynamic Coefficient of Friction (DCOF) | A137.1 | <=0.42 |
| Shade and Texture Rating | CTDA "V" | V3 |
| Facial Dimensions | C499 | Pass |
| Range of Thickness | C499 | Pass |
| Warping | C485 | Pass |
| Wedging | C502 | Pass |

Packaging Info

| Size | SF per carton | PC per carton |
|---------|---------------|---------------|
| 24"x48" | 15.50 | 2 |