



Roca

Alaska

Alaska

The Alaska White boasts graceful gray veining which give rise to interesting contrasts between its delicate veins and its homogeneous white base, making it a perfect ally for interior design.




Alaska White PO 24"x48" R

Polished Porcelain

◇ ≡ 24"x48" R

Alaska

Polished Porcelain



24"x48" R
60x120 cm



White



24"x48" R PO

Technical Specifications

CHARACTERISTICS	STANDARD	DECLARED ASTM
Water Absorption	C373	<=0.5%
Break Strength	C648	Min. 290
Scratch Hardness	MOH's Scale	3
Chemical Resistance	C650	Unaffected
Frost Resistance	C1026	Resistant
Group	See FAQ's	3
Deep Abrasion - Unglazed Tiles	C1243	Pass
PEI - Glazed Tiles	C1027	3
Minimum Bond Strength (PSI)	C482	165
Dynamic Coefficient of Friction (DCOF)	A137.1	<=0.42
Shade and Texture Rating	CTDA "V"	V3
Facial Dimensions	C499	Pass
Range of Thickness	C499	Pass
Warpage	C485	Pass
Wedging	C502	Pass

Packaging Info

Size	SF per carton	PC per carton	BX per pallet
24"x48" R	15.50	2	30