

# ST. TROPEZ

## TECHNICAL DATA



11190 NW 25th Street, Suite 100  
MIAMI, FL 33172  
www.rocatileusa.com

Format:	All formats Available	Type:	Ceramic Wall Tile
Colors:	All Colors Available	Thickness:	8.5 mm
Number of faces:	6	Recycled Content:	65% *Pre-Consumer

	ASTM Test	ISO Test	Value Required ANSI	Declared ASTM
WATER ABSORPTION	C373	ISO.10545/3	<7.0% < wa ≤20%	≤20%
BREAKING STRENGTH	C648	ISO.10545/4	≥ 125	≥ 125
SCRATCH HARDNESS	MOH's Scale	EN-101	-	Not Applicable
CHEMICAL RESISTANCE	C650	ISO-10545/13	Unaffected	Unaffected
SHADE AND TEXTURE RATING	CTDA "V"	-	-	V3
WARPAGE	C485	ISO-10545/2	0.75%	Pass
WEDGING	C502	ISO-10545/2	1.0% Max	Pass

\*Contains a percentage of pre-consumer recycled content superior to 25% which has been certified by Bureau Veritas.

Signature:  
Marketing and Product Department

  
MARKETING & PRODUCT DEPT  
11190 NW 25th Street, Suite 100  
MIAMI, FL 33172  
www.rocatileusa.com

Release  
06 / 12 / 2026